

suba 1
2
3

[illegible]

- 09685125 " 101000
1. A system for exchanging communications between a mobile device
a network site, the system comprising:
a conversion engine coupleable to a mobile device to accept a request
for a content from a network site, the request being signaled from the mobile
device in a first language and the content being structured in a second language,
the conversion engine being coupleable to the network site to retrieve the
content from the network site in response to receiving the request, the
conversion engine including logic to convert the content from the second
language to the first language and signaling the content to be rendered on the
mobile device,
wherein the first language provides on the mobile device for a single
input entry per page rendered from the network site, and the second language
allows for multiple input entries per page rendered from the network site.
2. The system of claim 1, wherein the conversion engine identifies one or
more input entries at the network site, and signals the input entries as selected
links to the mobile device.
- C:\TEMP\mobileshif0705-final.doc 20 Attorney Docket Number

1 3. The system of claim 2, wherein the conversion engine locates another
2 network site for the mobile device in response to a user of the mobile device
3 selecting each of the one or more input entries.

1 4. The system of claim 2, wherein the conversion engine creates a virtual
2 network site in response to a user of the mobile device selecting each of the one
3 or more input entries.

1 5. The system of claim 3, wherein the conversion engine identifies a text
2 entry field on the network site, and converts the text entry field to a selectable
3 link to a virtual network site created by the conversion engine, the virtual
4 network site for the text entry field providing a corresponding text entry field
5 for the mobile device.

6. The system of claim 3, wherein the conversion engine identifies a menu item on the network site, the menu item including a plurality of menu choices, the conversion engine converting the text entry field to a selectable link to a virtual network site created by the conversion engine, the virtual network site for the menu item displaying a link for each menu choice in the menu item.

1 7. The system of claim 3, wherein the conversion engine identifies a radio
2 button on the network site, the radio button being selectable to enter a Boolean
3 selection, the conversion engine converting the radio button into a selectable
4 link to a virtual network site created by the network site, the virtual network site
5 for radio button displaying a link for each Boolean value of the radio button.

1 8. The system of claim 3, wherein the conversion engine creates the virtual
2 network site after the user of the mobile device selects a link corresponding to
3 an input entry on the network site.

1 9. The system of claim 1, wherein the first language is a version of a
2 Handheld Device Markup Language (HDML), and the second language is a
3 version of Hypertext Markup Language (HTML).

1 10. The system of claim 9, wherein the second language is a version of
2 Compact HTML (CHTML).

1 11. The system of claim 1, wherein the conversion engine identifies an
2 internal link on the network site, the internal link on the network site locating a
3 second network site.

1 12. The system of claim 1, wherein the conversion engine formats the
2 internal link and includes the formatted internal links in the content signaled to
3 the mobile device, the formatted internal links being selectable on the mobile
4 device to generate a second request for the second network site without the
5 content engine converting the second request to the second language.

1 13. The system of claim 1, wherein the conversion engine includes a
2 conversion engine that is coupleable to a database, the database including an
3 instruction set for the mobile device, the instruction set being accessible by the
4 conversion engine to convert the request from the mobile device and the content
5 retrieved from the network site.

1 14. A method for exchanging communications between a mobile device and
2 a network site, the method comprising:

3 receiving a request to access a network site from a mobile device, the
4 request being received in a first language;

5 retrieving a content from the network site in the second language;

6 signaling the content to the mobile device in the first language;

7 wherein the first language allows for a single input entry per rendered
8 network page, and the second language allows for multiple input entries per
9 rendered network page.

1 15. The method of claim 14, further comprising converting the request from
2 the mobile device from the first language to the second language.

1 16. The method of claim 14, further comprising converting the content
2 retrieved from the network site from the second language to the first language.

1 17. The method of claim 14, wherein retrieving a content from the network
2 site includes identifying an internal link on the network site.

1 18. The method of claim 17, further comprising formatting the internal link
2 to be selectable on the mobile device to generate a second request, the mobile
3 device being able to generate the second request to be communicable with the
4 network site using the second language.

19. The method of claim 14, wherein retrieving a content from the network site includes identifying one or more input entries on the network site.

1 26. A method for exchanging communications between a mobile device and
2 a network site, the method comprising:
3 receiving a request to access a network site from a mobile device, the
4 request being received in a first language;
5 determining whether the network site is accessible using the first
6 language or a second language, and if the network site is accessible using the
7 second language, then
8 retrieving a content from the network site in the second language, and
9 signaling the content to the mobile device in the first language,
10 else if the network site is accessible using the first language, then
11 coupling the mobile device to the network site without converting the content
12 from the network site; and
13 wherein the first language allows for a single input entry per rendered
14 network page, and the second language allows for multiple input entries per
15 rendered network page.